



Decking G2 - 1x6 Classic Espresso 6ft-Long

Item #: XTR-DK20-G2-PP

PRODUCT DESCRIPTION: Classic Espresso 6ft-Long, 1x6 Decking, G2, Reversible, Rounded Edges, End-Match, Pre-Oiled dassoXTR Fused Bamboo, W.U.I. Compliant.

COLOR: Classic Espresso

SIZE: 3/4+" X 5-3/8+" X 6'

CONSTRUCTION: Thermalized Strand

:

FACE/BOTTOM MILLING: One Side Smooth, Another Side Reeded Face, 3mm Ridges/Valleys

LIN. FT. PER BUNDLE: 18.00

LIN. FT. PER PALLET: 1296.00

SQ.FT. PER BUNDLE: 8.09

SQ.FT. COVERAGE/BDL: 8.327

PRE-OILED : Yes - WOCA Natural Oil - Walnut Color

TYPE(S) OF INSTALLATION: Hidden fastener and plug on countersink face screw

Product Info

PRODUCT DESCRIPTION Classic Espresso 6ft-Long, 1x6 Decking, G2, Reversible, Rounded Edges, End-Match, Pre-Oiled dassoXTR Fused Bamboo, W.U.I. Compliant.

GRADE Fused Bamboo, Exterior Bamboo Grade

FACE/BOTTOM MILLING One Side Smooth, Another Side Reeded Face, 3mm Ridges/Valleys

BOARD EDGES PROFILE Sides rounded 3mm, ends beveled 2mm

PRE-OILED Yes - WOCA Natural Oil - Walnut Color

FINISHES Pre-Oiled

CROSS CUT SEALED Yes, Anchor Seal2

JOINERY End-Matched T&G, Metal Fastener, Screw & Plugs

GAP SIZE 3/16" or 0.1875 (4.762mm)

PLUGS AVAILABLE Yes, unfinished

FASTENING CLIPS & SCREWS AVAILABLE Yes, complete designed installation

FOR INDOOR USE? Yes, zero VOC, indoor safe, material is food grade safe.

CONSTRUCTION Thermalized Strand

PROCESS OR TREATMENT Thermalized and Fused

BINDING PROCESS Fusion Press

BINDING AGENT Phenolic Resin (same resin type in bowling ball)

MARKET NAME Fused Bamboo

THICKNESS (NOMINAL)	1
THICKNESS (FRACTION)	3/4+"
THICKNESS (DECIMAL)	0.79 inches
WIDTH (NOMINAL)	6
WIDTH (FRACTION)	5-3/8+"
WIDTH (DECIMAL)	5.39 inches
WIDTH IN FT (INCLUDE GAP)	0.463
WIDTH IN METER (INCLUDE GAP)	0.141
LENGTH (DECIMAL)	72 inches
LENGTH/LENGTH RANGE	6'
THICKNESS (MM)	20 mm
WIDTH (MM)	137 mm
NUMERIC MM WIDTH FOR CALCULATIONS	137
LENGTH (MM)	1,829 mm

Packaging

BUNDLE DIMENSION (INCH)	2.5" x 5-1/2" x 73"
PIECES PER BUNDLE (N)	3 (18 Lin.ft.)
BUNDLES PER PALLET	72 (8 row x 9 layer)
SQ.FT. PER BUNDLE	8.09
SQ.FT. PER PALLET	583.20
SQ.FT. COVERAGE/BDL	8.327
LIN.FT. PER PIECE	6
LIN.FT. PER BUNDLE	18
LIN.FT. PER PALLET	1296
IB PER LIN.FT.	2.2
IB PER BUNDLE	39.6
IB PER PALLET	2851.2
IB PER PALLET SHOES	55
TOTAL WEIGHT (LB)	2890.8
PALLET+SHOES DIMENSION (INCH)	H28" x W44" x L73"
BUNDLE DIMENSION (MM)	64mm x 140mm x 1840mm
PIECES PER BUNDLE (M)	3 (5.487 Meter long)
BUNDLES PER PALLET (M)	72 (8 row x 9 layer)
M2 PER BUNDLE	0.752
M2 PER PALLET	54.12
M2 COVERAGE/BDL	0.774
METER PER PIECE	1.829
METER PER BUNDLE	5.487
METER PER PALLET	395.06
KG PER METER	3.274
KG PER BUNDLE	17.962
KG PER PALLET	1293.29
KG PER PALLET SHOES	25
TOTAL WEIGHT (KG)	1311.29

PALLET+SHOES DIMENSION (MM) H705mm x W1096mm x L1840mm

Technical Info

HARDNESS 3,820 lbf Janka rating

JOIST SPAN (ON CENTER) 12", 16" or 24" on-center

JOIST SPAN MAXIMUM 24" (the product can actually span greater than 24", but building codes limit joist span)

GAP SIZE DETERMINATION Gap size is determined by the type of fastener chosen. Panda Claw give a 3/16" gap install with 3/16" spacer and deck wrench.

FIRE RATING ASTM E84, Class A & WUI Approved

RECOMMENDED SITE FINISH Touch up only, do not recoat before exposed 6 month to ambient.

Eco Properties

FORMALDEHYDE EMISSION FROM BINDERS E0 / F****

FSC CERTIFIED AVAILABILITY Yes - as Special Order

Installation / Warranty

TYPE(S) OF INSTALLATION Hidden fastener and plug on countersink face screw

CORROSION INFORMATION For applications exposed to salt air, near large bodies of water, swimming pools or other areas where corrosion is more likely to occur, always use Grade 316 stainless steel screws.

WARRANTY RESIDENTIAL 50 Years

WARRANTY COMMERCIAL 10 Years

Copyright © 2019 dasso.XTR | dassoXTR.com | +1 855.774.0002 | 404.691.6872 | info@dassoXTR.com | 6060 Boat Rock
Blvd SW, Suite 800, Atlanta, GA 30336