



Decking G2 - 1x6 Classic Espresso 6ft-Long

ITEM # XTR-DK20-G2-PP

PRODUCT SPECIFICATIONS

PRODUCT DESCRIPTION: Classic Espresso 6ft-Long, 1x6 Decking, G2, Reversible, Rounded Edges, End-Match, Pre-Oiled dassoXTR Fused Bamboo, W.U.I. Compliant.

COLOR: Classic Espresso

SIZE: 3/4" X 5-3/8" X 6'

CONSTRUCTION: Thermalized Strand

:

FACE/BOTTOM MILLING: One Side Smooth, Another Side Reeded Face, 3mm Ridges/Valleys

LIN. FT. PER BUNDLE: 18.00

LIN. FT. PER PALLET: 1296.00

SQ.FT. PER BUNDLE: 8.09

SQ.FT. COVERAGE/BDL: 8.327

PRE-OILED: Yes, WOCA Natural Oil - Walnut Color

TYPE(S) OF INSTALLATION: Hidden fastener and plug on countersink face screw

PRODUCT INFO

PRODUCT DESCRIPTION: Classic Espresso 6ft-Long, 1x6 Decking, G2, Reversible, Rounded Edges, End-Match, Pre-Oiled dassoXTR Fused Bamboo, W.U.I. Compliant.

GRADE: Fused Bamboo, Exterior Bamboo Grade

FACE/BOTTOM MILLING: One Side Smooth, Another Side Reeded Face, 3mm Ridges/Valleys

BOARD EDGES PROFILE: Sides rounded 3mm, ends beveled 2mm

PRE-OILED: Yes, WOCA Natural Oil - Walnut Color

FINISHES: Pre-Oiled

CROSS CUT SEALED: Yes, Anchor Seal2

JOINERY: End-Matched T&G, Metal Fastener, Screw & Plugs

GAP SIZE: 3/16" or 0.1875 (4.762mm)

PLUGS AVAILABLE: Yes, unfinished

FASTENING CLIPS & SCREWS AVAILABLE: Yes, complete designed installation

FOR INDOOR USE? Yes, zero VOC, indoor safe, material is food grade safe.

CONSTRUCTION: Thermalized Strand

PROCESS OR TREATMENT	Thermalized and Fused
BINDING PROCESS	Fusion Press
BINDING AGENT	Phenolic Resin (same resin type in bowling ball)
MARKET NAME	Fused Bamboo
THICKNESS (NOMINAL)	1
THICKNESS ~F (INCH)	3/4+"
THICKNESS ~D (INCH)	0.79 inches
WIDTH (NOMINAL)	6
WIDTH ~F (INCH)	5-3/8+"
WIDTH ~D (INCH)	5.39 inches
WIDTH IN FT (INCLUDE GAP)	0.463
WIDTH IN METER (INCLUDE GAP)	0.141
LENGTH ~D (INCH)	72 inches
LENGTH/LENGTH RANGE	6'
THICKNESS (MM)	20 mm
WIDTH (MM)	137 mm
NUMERIC MM WIDTH FOR CALCULATIONS	137
LENGTH (MM)	1,829 mm

PACKAGING

BUNDLE DIMENSION (IN)	2.5" x 5-1/2" x 73"
PIECES PER BUNDLE (N)	3 (18 Lin.ft.)
SQ.FT. PER BUNDLE	8.09
SQ.FT. PER PALLET	583.20
SQ.FT. COVERAGE/BDL	8.327
LIN.FT. PER PIECE	6
LIN.FT. PER BUNDLE	18
LIN.FT. PER PALLET	1296
IB PER LIN.FT.	2.2
IB PER BUNDLE	39.6
IB PER PALLET	2851.2
IB PER PALLET SHOES	55
TOTAL WEIGHT (LB)	2890.8
PALLET+SHOES DIMENSION (IN)	H28" x W44" x L73"
CONTAINER CAN LOAD	20 GP/18 Pallets
BUNDLE DIMENSION (MM)	64mm x 140mm x 1840mm
PIECES PER BUNDLE (M)	3 (5.487 Meter long)
BUNDLES PER PALLET	72
M2 PER BUNDLE	0.752
M2 PER PALLET	54.12
M2 COVERAGE/BDL	0.774
METER PER PIECE	1.829
METER PER BUNDLE	5.487

METER PER PALLET	395.06
KG PER METER	3.274
KG PER BUNDLE	17.962
KG PER PALLET	1293.29
KG PER PALLET SHOES	25
TOTAL WEIGHT (KG)	1311.29
PALLET+SHOES DIMENSION (MM)	H705mm x W1096mm x L1840mm

TECHNICAL INFO

HARDNESS	3,820 lbf Janka rating
JOIST SPAN (ON CENTER)	12", 16" or 24" on-center
JOIST SPAN MAXIMUM	24" (the product can actually span greater than 24", but building codes limit joist span)
GAP SIZE DETERMINATION with 3/16" spacer and deck wrench.	Gap size is determined by the type of fastener chosen. Panda Claw give a 3/16" gap install
FIRE RATING	ASTME84, Class A & WUI Approved
RECOMMENDED SITE FINISH	Touch up only, do not recoat before exposed 6 month to ambient.

ECO PROPERTIES

FORMALDEHYDE EMISSION FROM BINDERS	E0 / F****
FSC CERTIFIED AVAILABILITY	Yes - as Special Order

INSTALLATION / WARRANTY

TYPE(S) OF INSTALLATION	Hidden fastener and plug on countersink face screw
CORROSION INFORMATION	For applications exposed to salt air, near large bodies of water, swimming pools or other areas where corrosion is more likely to occur, always use Grade 316 stainless steel screws.
WARRANTY RESIDENTIAL	50 Years
WARRANTY COMMERCIAL	10 Years