


MAR VISTA SUSTAINABLE ADDITION PROJECT Los Angeles, CA, USA

PROJECT PROFILE







MAR VISTA SUSTAINABLE ADDITION PROJECT

OUTDOOR BAMBOO DECKING

architect: Audrey Sato, Sato Architects, Inc.

builder: Bryan Capper location: Los Angeles, CA client: Private Residence

product: dassoXTR Fused Bamboo®

Decking and Soffit

quantity: 135 sq/ft date: 1/10/2021



WOCA Oil

T&G

The dasso Group, based in Hangzhou, China, has been the world's leader in innovative bamboo products for more than two decades. With 10 manufacturing facilities, over 1,000 employees, a Design and Research Center, and over 40 patents to date, dasso's mission is in to advance the innovative use of bamboo throughout the world.

AVAILABLE IN 2 COLORS



PATENTED: CHINA, RUSSIA, AUSTRALIA, USA, EU, MALAYSIA, SINGAPORE

RESIDENTIAL DECKING

| Item Code | Dimensions | Edges | Ends | Primed with | | | |
|--------------------|---|--------------------|------|------------------|--|--|--|
| XTR-DK20-G0-PP | 20 mm x 137 mm x 1829 mm 3/4+" x 5-3/8+" x 72" | | T&G | ₩OCA Oil | | | |
| COMMERCIAL DECKING | | | | | | | |
| Item Code | Dimensions | Edges | Ends | Primed with | | | |

TECHNICAL HIGHLIGHTS

XTR-DK40-G0-PP

» Unsupported end-match Joint has a span rating of 100 psf.* *Per ASTM D7032 over 16" framing

40 mm x 137 mm x 1829 mm

- » Class A fire rating per ASTM E84.
- » More dense than Ipe.1

DESIGN FEATURES

- » Only decking on the market with an end joint that can be installed off the joist.
- » Can stain to a variety of colors using our XTR Guard system.
- » The look and feel of a natural wood product. Performs like dense tropical hardwoods.
- » Offers the consistent quality of a manufactured composite product.

INSTALLATION BENEFITS


- » Available pre-primed for subsequent on-site topcoating.
- » Side-grooved for hidden fastening or can be face-screwed with screws exposed or plugged using dasso.XTR plugs.
- » Decking is 6' long and end-matched for installation on the joist (on 12"/18"/24" centers) or by coverage method off the joist on 16"
- » Less time, less labor, less waste and easier installation.

COMPARISON CHART

| sкu | dassoXTR | dassoXTR | lpe/Brazil- | Meranti | Western |
|--|----------------------|----------------------|----------------------|-----------------------|----------------------|
| | Espresso | Cognac | ian Walnut | Batu | Red Cedar |
| Density | 69 | 75 | 66 | 53 | 23 |
| lb/ft3(kg/m3) | (1,100) | (1,200) | (1,060) | (850) | (370) |
| Strength MQ psi(MPa) | 11,922 | 17,730 | 19,173 | 17,259 | 7,498 |
| | (82) | (122) | (132) | (119) | (52) |
| Stiffness MOE | 2,101 | 2,013 | 3,200 | 245 | 1,100 |
| 1000psi(MPa) | (14,490) | (13,880) | (22,070) | (16,950) | (7,584) |
| Janka Hardnes | 16,992 | 17,659 | 15,620 | 7,117 | 3,110 |
| Newton(lbf) | (3,820) | (3,970) | (3,510) | (1,600) | (700) |
| Shrinkage longitude % width % thickness % | 0.02 0.40 1.90 | 0.06 1.20 3.70 | 0.16 5.90 7.20 | 0.17 5.50 10.10 | 0.20 2.40 5.00 |









END MATCH

All of our decking is end-matched for ease and improved quality of installation and to provide full coverage on or off the joist. Learn more at dassoXTR.com.

30 YEAR LIMITED WARRANTY

dasso.XTR products are manufactured using a patented process to ensure lasting outdoor beauty and enjoyment. Periodic recoating with XTR Guard is recommended to maintain its rich color. Please follow our maintenance instructions.

Visit dassoXTR.com for copies of our installation and maintenance instructions and warranties.